MIRK
www.mirkinc.us
Aerial Man Lifts
Digger Trucks

THE MIRK ADVANTAGE

7629 Chippewa Rd • Orrville, Ohio 44667
330-669-2000
Fax: 330-669-3732

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 004R

UNDERGROUND PULLER:
CONDUX TESMEC MODEL # ARS510 S.N. 5151
HYDRAULIC PULLER (TRAILER)
THE ARS510 OFFERS 15,750 lbf (70 kN) OF PULLING FORCE AND IS DESIGNED FOR STRINGING ONE ROPE UP TO 5/8" (16MM) IN DIAMETER. THE BULL-WHEEL GROOVES ON THE ARS510 ARE MADE FROM HEAT TREATED STEEL.
CLOSED HYDRAULIC CIRCUIT FOR STEPLESS SPEED VARIATION IN BOTH ROTATING DIRECTIONS
NEGATIVE SELF-ACTING HYDRAULIC BRAKE
HYDRAULIC DYNAMOMETER WITH SET POINT AND AUTOMATIC CONTROL OF MAXIMUM PULL.
HYDRAULIC OIL COOLING SYSTEM.
DIGITAL METER COUNTER INCLUDED IN DLR.

UNDER GROUND PULLER:
WATER COOLED DIESEL ENGINE 81 HP (60 KW)
BULL-WHEEL DIAMETER 15 3/4" (400 MM)
2,500 FEET OF BRAIDED ANTITWIST ROPE 5/8" (16 MM)
MAXIMUM PULL 15,750 LBF (70KN)
SPEED @ MAX. PULL 1.1 MPH (1.8 KM/H)
MAX. PULL SPEED 2.5 MPH (4.0 KM/H)
PULL @ MAX SPEED 7,200 LBF (32 KN)
BUILT IN REEL WINDER WITH AUTOMATIC LEVEL WIND AND REEL TO HOLD 3,280 FT. 5/8 (16MM) WIRE ROPE
NOISE REDUCTION PROTECTION
EQUIPMENT FOR ELECTRONIC STRINGING PARAMETER RECORDER. PULL PRE-SETTING SYSTEM
HIGH PULL/LOW SPEED & LOW PULL/ HIGH SPEED SELECTION. ELECTRONIC PULL AND SPEED RECORDER.
CONTROL FOR PULL/ PAYOUT

TRAILER SPECS.
TRAILER V.I.N. 1C9HU1622H0032248
D.O.T. DUAL AXLE TRAILER FOR TRANSPORT
D.O.T. SPEC. LIGHTING & BREAK-A-WAY
WEIGHT WITH WIRE ROPE 7,800 LBS.
OVERALL LENGTH 192 INCHES
OVERALL WIDTH 85 INCHES
OVERALL HEIGHT 75 INCHES
PINTLE HITCH LUNETTE EYE FOR TOWING
MECHANICAL FRONT STABILIZER
MANUAL CRANK TONGUE JACK

CALL US FOR ALL YOUR EQUIPMENT NEEDS:BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS
TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!!!