

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 032P

HYDRAULIC UNDERGROUND PULLER:

CONDUX MODEL ARS701 40,000 LB. PULLER V.I.N. # 1Z9PU1623EM026167 S.N. 06463 **BULL-WHEEL DIAMETER: 23.6 INCHES NEGATIVE SELF-ACTING HYDRAULIC BRAKE** HYD. DYNAMETER WITH SET POINT & AUTO. CON-TROL OF MAXIMUM PULL. HYDRAULIC OIL COOLING SYSTEM. HYD. QUICK CONNECTS TO CONTROL A SEPARATE REEL WINDER INSTEAD OF BUILT IN ONE. **CLOSED HYD. CIRCUIT FOR STEPLESS SPEED VARIA-**TION IN BOTH ROTATING DIRECTIONS. MACHINE IS **PROVIDED WITH A PULL PRE-SETTING SYSTEM THAT** MAINTAINS THE PRE SET PULLING VALUE (ALSO WHEN THE SPEED IS REDUCED TO "0") BY AUTOMAT-**ICALLY ADJUSTING THE OPERATION SPEED AC-**CORDING TO THE FRICTION AND UNEXPECTED LOADS WHICH MAY OCCUR.



HYD. EXTERNAL DRUM SAFETY CLAMP TO HOLD CONDUCTOR AGAINST PULLING DRUM OPTIONAL ELECTRONICPULL AND SPEED RECORDER ADJUSTABLE SIDE TO SIDE FAIRLEAD ROLLER FOR PULLING LINE. AIR BRAKES APPROX. TOTAL WEIGHT: 19,000 LBS.



PULLER PERFORMANCE: MAX PULL: 40,300 LBF SPEED @ MAX. PULL: 1.4 MPH MAX. SPEED: 3.1 MPH PULL @ MAX. SPEED: 17,985 LBF 280 HP DIESEL ENGINE GROUNDING CONNECTION POINT HYDRAULIC FRONT STABILIZER JACK



CALL US FOR ALL YOUR EQUIPMENT NEEDS:BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!!