

RENTALS. SALES AND SERVICE NEW and USED ullet AERIAL PLATFORMS ullet DIGGER-DERRICK TRUCKS ullet Specialty equipment

CONDUX HYDRAULIC TENSIONER:

2013 FRB 616 HYDRAULIC TENSIONER PROVIDES UP TO 31,473 LBS. OF TENSIONING FORCE. DESIGNED FOR STRING-ING ONE OR TWO ROPES OR BUNDLED CONDUCTORS WITH TWO PAIRS OF COMPLETELY INDEPENDENT BULL-WHEELS. **INDUSTRY LEADING FEATURES LIKE NEGATIVE SELF-**ACTING HYDRAULIC BRAKE, HYDRAULIC DYNAMOMETER, AND HYDRAULIC COOLING SYSTEM. BULL-WHEELS COME STANDARD WITH INTERCHANGEABLE NYLON SECTORS. FRB616 HYDRAULICALLY CONTROLLED SYSTEM HELPS ELIM-INATE CONDUCTOR GALLOPING. MAKING THIS ONE OF THE SAFEST PULLER/ TENSIONER ON THE MARKET TODAY. HYDRAULIC TRANSMISSION: 2 HYDRAULIC HALF CLOSED CIRCUITS THAT ALLOW VERY SENSITIVE TENSIONING CON-TROL AND NEGLIGIBLE DEVIATIONS OF TENSION IN CASE OF SPEED CHANGE. THE MACHINE IS PROVIDED WITH TENSION PRE-SETTING SYSTEM. 3 POSITION OPTIONAL GEARBOX **NEUTRAL POSITION, LOW TENSION, AND NOMINAL TENSION.**



MIRK # 046N FRB-616

PULL BACK PERFORMANCE: S.N. 6471 MAX. PULL—2 X 15,737 LBS. OR 1 X 31,473 LBS. MAXIMUM SPEED— 0.4 MPH.

TENSIONER PERFORMANCE:

MAX. TENSION—2 X 15,737 LBS OR 1 X 31,473 LBS MAX. SPEED— 3.1 MPH **BULL WHEEL DIAMETER: 66 15/16 INCHES** MAX. CONDUCTOR DIAM. 1 13/16 INCHES 64 H.P. DIESEL ENGINE LIQUID COOLED 12 VOLT ELECTRICAL SYSTEM HYD. ACTUATED FRONT PLOW STABILIZER CONTROL INSTRUMENTS FOR HYD. SYSTEM AND DIESEL ENGINE CUMMINS MODEL B3.3 (65 HP) 3.261 LITER SN. 68336626 (2) HYD. CONDUCTOR CLAMPS FOR REEL CHANGE



CONFIGURATION:

2 NEGATIVE SELF-ACTING HYD. BRAKES 2 HYD. DYNAMOMETERS HYDRAULIC OIL COOLING SYSTEM **2 DIGITAL FOOTAGE COUNTERS 2 DIGITAL SPEED METERS** HYDRAULIC POWER PACK TO CONTROL UP TO 2 SEPA-**RATE REEL STANDS W/ HYD. HEAD NET WEIGHT: 20,750 LBS**

OVERALL LENGTH: 236 IN. OVERALL WIDTH: 96 IN.

HEIGHT: 135 IN.

