

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

UNDERGROUND PULLER:

2020 THALER MODEL # KE-SP 60100 SERIAL NUMBER: W09SPX205LBT06167 THE 60100 OFFERS 22,000 lbf (100kN) OF PULLING FORCE AND IS DESIGNED FOR STRINGING ONE CABLE UP TO 5/8" (16MM) IN DIAMETER. THE BULL-WHEEL GROOVES ON THE 60100 ARE MADE FROM HEAT TREATED STEEL.

CLOSED HYDRAULIC CIRCUIT FOR STEPLESS SPEED VARIATION IN BOTH ROTATING DIRECTIONS NEGATIVE SELF-ACTING HYDRAULIC BRAKE AUTOMATIC CONTROL OF MAXIMUM PULL. HYDRAULIC OIL COOLING SYSTEM. DIGITAL METER COUNTER



TRAILER SPECS.

D.O.T. TANDEM AXLE TRAILER FOR TRANSPORT D.O.T. SPEC. LIGHTING & BREAK-A-WAY GVWR: 11,023 LBS.

PINTLE HITCH LUNETTE EYE FOR TOWING
(2) MANUAL STABILIZER LEGS @ REAR
MANUAL CRANK TONGUE JACK

UNIT SHIPPING DIMENSIONS:

OVERALL LENGTH 180 INCHES OVERALL WIDTH 77 INCHES OVERALL HEIGHT 84 INCHES

WEIGHT LBS.

MIRK # 052R



UNDER GROUND PULLER:

KOHLER 3 CYLINDER DIESEL ENGINE 56 HP (TIER 4)
ELECTRONIC RECORDER SYSTEM TM 3000 W/ USB PORT
MAXIMUM ROPE DIAMETER 5/8" (16 MM)
MAXIMUM PULL 22,000 LBF (100KN)
ADJUSTABLE BOOM ASSEMBLY FOR 4' TO 16' MANHOLES
BUILT IN REEL WINDER WITH AUTOMATIC LEVEL WIND
AND REEL TO HOLD 3,051 FT. 5/8 16MM WIRE ROPE
NOISE REDUCTION PROTECTION
PULL PRE-SETTING SYSTEM
ELECTRONIC PULL AND SPEED RECORDER.
WIRED DEADMAN SWITCH FOR PULL/ PAYOUT
UNDERGROUND CABLE PULLING ATTACHMENT
EMERGENCY STOP BUTTON

