

## RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

## **UNDERGROUND PULLER:**

CONDUX TESMEC MODEL # ARS607 HYDRAULIC UNDERGROUND PULLER (TRAILER) THE ARS607 OFFERS 22,481 lbf (100kN) OF PULLING FORCE AND IS DESIGNED FOR STRINGING ONE CABLE UP TO 5/8" (16MM) IN DIAMETER. THE BULL-WHEEL GROOVES ON THE ARS607 ARE MADE FROM HEAT TREATED STEEL. CLOSED HYDRAULIC CIRCUIT FOR STEPLESS SPEED VARIATION IN BOTH ROTATING DIRECTIONS NEGATIVE SELF-ACTING HYDRAULIC BRAKE HYDRAULIC DYNAMOMETER WITH SET POINT AND AUTOMATIC CONTROL OF MAXIMUM PULL. HYDRAULIC OIL COOLING SYSTEM. DIGITAL METER COUNTER



## **TRAILER SPECS.**

D.O.T. TANDEM AXLE TRAILER FOR TRANSPORT ELECTRIC PARKING BRAKE. D.O.T. SPEC. LIGHTING & BREAK-A-WAY WEIGHT (W/O ROPE) 5,512 LBS. (2500 KG) OVERALL LENGTH 111 INCHES OVERALL WIDTH 95 INCHES OVERALL HEIGHT 73 INCHES PINTLE HITCH LUNETTE EYE FOR TOWING (4) MANUAL STABILIZER LEGS. MANUAL CRANK TONGUE JACK

## MIRK # 055N



UNDER GROUND PULLER: HYD ROPE CLAMP FOR REEL CHANGE OPERATIONS WATER COOLED DIESEL ENGINE 48 HP (36 KW) BULL-WHEEL DIAMETER 15 3/4" (400 MM) 5/8"<sup>•</sup> (16 MM) MAXIMUM ROPE DIAMETER MAXIMUM PULL 22,841 LBF (100KN) SPEED @ MAX. PULL 0.3 MPH (4.0 KM/H) MAX. PULL SPEED 2.5 MPH (4.0 KM/H) 2,810 LBF (12.5 KN) PULL @ MAX SPEED **BUILT IN REEL WINDER WITH AUTOMATIC LEVEL WIND** NOISE REDUCTION PROTECTION EQUIPMENT FOR ELECTRONIC STRINGING PARAMETER **RECORDER. PULL PRE-SETTING SYS. HIGH PULL/LOW SPEED & LOW PULL/ HIGH SPEED** SELECTION. ELECTRONIC PULL AND SPEED RECORDER. **ROLLER DEVICE FOR UNDERGROUND** 



CALL US FOR ALL YOUR EQUIPMENT NEEDS:BUCKETS\*DIGGERS\*PULLERS\*CRANES\*SKIDDERS TRACK MACHINES\*TRAILERS\*CHIPPERS\*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!!