

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

SINGLE DRUM PULLER:

SHERMAN & REILLY MODEL # P-6048-D-T
HYDRAULIC 6,000 LB. PULLER
V.I.N. 123WM181361T18071
JOHN DEERE 4.5 LITER DIESEL ENGINE
PE4045T4-48T44 (TIER-2)
MAX. PULL 6,000 LBS. TOP OF DRUM
SPEED: UP TO 4.0 M.P.H.
2 1/2" O.D. ARBOR BAR
FULLY HYDRAULIC DRIVE SYSTEM
20 GAL. HYD. RESERVOIR
PAY-OFF BRAKE (OVERSPIN)
HYD. LEVEL WIND ARM WITH ROLLERS
OPERATORS PROTECTIVE SCREEN W/ SEAT
HOLDING BRAKE: RATCHET / PAWL (PULL MODE ONLY)
30 GALLON ALUMINUM FUEL TANK



DIMENSIONAL DATA:

SHIPPING WEIGHT: 11,000 LBS. WITH ROPE

OVERALL LENGTH: 17'3"
OVERALL WIDTH: 8'

HEIGHT TO TOP OF CONTROL PANEL: 9'

STEEL TREADPLATE FENDERS

D.O.T. SPEC. LIGHTING

18,000 FT. OF 5/8" YALEX PE-12 ROPE ON DRUM.

CURRENT REEL DIMENSIONS:

60" O.D. X 24" DRUM X 36" I.D. WIDE

MAX. ROPE CAPACITY:

18,000' OF 5/8" SYNTHETIC ROPE

8 HOLE BUDD WHEELS W/ ST235/85R16 TIRES

OIL BATH HUBS

MIRK # 068P



MAXIMUM CONDUCTOR REEL IT WILL HOLD:

44" MAX. WIDTH
72" MAX. O.D. DIAMETER
6,000 LBS. MAX. WEIGHT
ADJUSTABLE PINTLE STYLE HITCH
SAFETY CHAINS
7 PRONGE LARGE TRAILER PLUG
G.V.W.R. 11,500 LBS.
SINGLE AXLE DUAL WHEEL
ELECTRIC BRAKES
HYD. TONGUE JACK
HYDRAULIC REAR STABILIZER LEGS

