

MIRK

www.mirkinc.us

Aerial Man Lifts
Digger Trucks

THE MIRK ADVANTAGE



7629 Chippewa Rd • Orrville, Ohio 44667

330-669-2000

Fax: 330-669-3732

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 071N

BULLWHEEL TENSIONER:

WAGNER SMITH MODEL T- BWT—4—38RC
TRAILER MOUNTED 38" BOTTOM OF GROOVE
SINGLE CONDUCTOR BULLWHEEL TENSIONER
V.I.N. 1W9PT1825PB161067
MAXIMUM LINE TENSION RATING
IS 4,000 LBS. AT UP TO 4 MPH LINE SPEED
MAJOR OPERATING SAFETY FEATURES:
BULLWHEEL BRAKES ARE SMOOTH RUNNING ME-
CHANICAL CALIPERS. ALL UNIT CONTROLS
ARE LOCATED AT THE OPERATORS STATION
OFF THE GROUND, FOR OPERATOR SAFETY.
LARGE DIAMETER FAIRLEAD ROLLOR ASSEMBLY
IS PROVIDED TO REDUCE BENDING
RADIUS ON INPUT SIDE.



TENSIONER SPECIFICATIONS:

DIAMETER:	38" (BOTTOM OF GROVE)
GROOVE DIAMETER:	1.50"
# OF GROOVES:	5
REPLACEABLE SEG.	YES
BULLWHEEL LINING:	ELASTOMER (BOLT ON)
TENS. BRAKES:	MECH. CALIPER DISC
BRAKE DISC:	24" DIAM.
BULLWHEELS:	38" BOTTOM OF GROOVE
MAXIMUM TENSION:	4,000 LBS.
LINE SPEED (AVG.)	0—4 MPH
REEL CARRIER:	104" MAX. DIAM, 60" MAX. WIDTH
	10,000 LB. MAX WEIGHT, 2 3/4" ARBOR BAR



DIMENSIONAL DATA:

UNIT LENGTH: 19 FT.
UNIT WIDTH: 8 FT. 0 IN.
UNIT HEIGHT: 9 FT. 4 IN.
NET WEIGHT: 5,820 LBS. (APPROX.)
TANDEM AXLE TRAILER MOUNTED
LEAF SPRING SUSPENSION
ELECTRIC BRAKES W/ BREAK A WAY
ADJ. 3" LUNETTE EYE FRONT HITCH
MECHANICAL FRONT JACK
9R 17.5 RADIAL TIRES LOAD RANGE H
REAR PIN TYPE STABILIZERS



**CALL US FOR ALL YOUR EQUIPMENT NEEDS: BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS
TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!**