

MIRK

www.mirkinc.us

Aerial Man Lifts
Digger Trucks

THE MIRK ADVANTAGE



7629 Chippewa Rd • Orrville, Ohio 44667

330-669-2000

Fax: 330-669-3732

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 078P

UNDERGROUND PULLER:

CONDUX TESMEC MODEL # ARS610 S.N. 09190
HYDRAULIC UNDERGROUND PULLER (TRAILER)
THE ARS610 OFFERS 22,500 lbf (100kN) OF PULLING FORCE AND IS DESIGNED FOR STRINGING ONE CABLE UP TO 5/8" (16MM) IN DIAMETER. THE BULL-WHEEL GROOVES ON THE ARS610 ARE MADE FROM HEAT TREATED STEEL.
CLOSED HYDRAULIC CIRCUIT FOR STEPLESS SPEED VARIATION IN BOTH ROTATING DIRECTIONS
NEGATIVE SELF-ACTING HYDRAULIC BRAKE
HYDRAULIC DYNAMOMETER WITH SET POINT AND AUTOMATIC CONTROL OF MAXIMUM PULL.
ELECTRONIC OIL COOLING SYSTEM.
DIGITAL METER COUNTER



UNDER GROUND PULLER:

WATER COOLED DIESEL ENGINE 75 HP (55 KW)
BULL-WHEEL DIAMETER 15 3/4" (400 MM)
4,920 FEET OF BRAIDED ANTITWIST ROPE 5/8" (16 MM)
MAXIMUM PULL 22,500 LBF (100KN)
SPEED @ MAX. PULL 0.6 MPH (0.9 KM/H)
MAX. PULL SPEED 1.2 MPH (2.0 KM/H)
PULL @ MAX SPEED 9,000 LBF (40 KN)
BUILT IN REEL WINDER WITH AUTOMATIC LEVEL WIND AND REEL TO HOLD 4,920 FT. 5/8 (16MM) WIRE ROPE
NOISE REDUCTION PROTECTION
EQUIPMENT FOR ELECTRONIC STRINGING PARAMETER RECORDER. PULL PRE-SETTING SYSTEM
HIGH PULL/LOW SPEED & LOW PULL/ HIGH SPEED SELECTION. ELECTRONIC PULL AND SPEED RECORDER.
RADIO REMOTE CONTROL FOR PULL/ PAYOUT
UNDERGROUND CABLE PULLING ATTACHMENT

TRAILER SPECS.

TRAILER V.I.N. 1Z9PU1215JM026209
D.O.T. SINGLE AXLE TRAILER FOR TRANSPORT
D.O.T. SPEC. LIGHTING & BREAK-A-WAY
WEIGHT WITH WIRE ROPE 12,260 LBS.
OVERALL LENGTH 160 INCHES
OVERALL WIDTH 96 INCHES
OVERALL HEIGHT 101 INCHES
PINTLE HITCH LUNETTE EYE FOR TOWING
(2) MANUAL AND (2) HYDRAULIC STABILIZER LEGS.
MANUAL CRANK TONGUE JACK



**CALL US FOR ALL YOUR EQUIPMENT NEEDS: BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS
TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!**