

**MIRK**

www.mirkinc.us

Aerial Man Lifts  
Digger Trucks

**THE MIRK ADVANTAGE**



7629 Chippewa Rd • Orrville, Ohio 44667

**330-669-2000**

Fax: 330-669-3732

**RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT**

**V-GROOVE PULLER/ TENSIONER:**

TSE MODEL PTV-100/ 72 PULLER/ TENSIONER  
S.N. 10-3801-01  
MAX. CONTINUOUS LINE PULL: 10,000 LBS. @ 4 MPH  
MAX. INTERMITTENT LINE PULL: 11,000 LBS.  
INFINITELY VARIABLE SPEED: 0 TO 4 MPH  
SPRING APPLIED, HYD RELEASED HOLDING BRAKES  
BULLWHEEL DIAMETER: 72 INCHES  
BOTTOM OF GROVE DIAMETER: 65.5 INCHES  
WITH INFINITE SPEED & LINE PULL CONTROL WITH  
OVERPULL PROTECTION  
FULLY HYDROSTATIC DRIVE SYSTEM  
OSCILLATING BULLWHEEL FOR MINIMAL FLEET ANGLE  
ON CONDUCTOR OR ROPE  
CONTROL CONSOLE WITH OPERATORS SEAT  
JOHN DEERE DIESEL ENGINE (173 H.P.) WATER COOLED  
ENGINE S.N. PE6068HF285

**MIRK # 082P**



**ELASTOMER BULLWHEEL SEGMENTS**  
THE MACHINE DESIGN INCORPORATES A PIVOTING  
BULLWHEEL WHICH AUTOMATICALLY ALIGNS THE  
BULLWHEEL WITH THE POINT ON THE REEL FROM  
WHICH THE CONDUCTOR IS BEING PAYED OFF. DURING  
THE PULLING MODE THE OPERATOR CONTROLS THE  
BULLWHEEL MOVEMENT TO LEVELWIND THE PULLED  
CABLE ONTO THE STORAGE REEL  
**SELF LOADING REAR MOUNTED REEL WINDER:**  
MAXIMUM REEL SIZE: 96" X 53"  
MAXIMUM REEL WEIGHT (HIGHWAY) 11,000 LBS.  
MAXIMUM REEL WEIGHT (JOBSITE) 16,000 LBS.

**TRAILER: VI# 1T92C2821AS268038**

TANDEM AXLE TRAILER (ELECTRIC BRAKES)  
G.V.W.R. 33,000 LBS.  
15,000 LBS. PER AXLE  
11.00 R20 RADIAL TIRES ON 20 X 8 RIMS  
3" PINTLE HITCH ADJUSTABLE  
HYDRAULIC TONGUE JACK  
2 REAR HYDRAULIC DROP LEG JACKS  
BREAKAWAY SAFETY CHAINS W/ HOOKS  
7 PRONG TRAILER PLUG (ROUND)  
LENGTH: 25' 6" WIDTH: 8'4" HEIGHT: 11' 1"  
WEIGHT: APPROX. 25,000 LBS.  
OPTIONAL : SPLIT REEL IS AVAILABLE



**CALL US FOR ALL YOUR EQUIPMENT**

**NEEDS:BUCKETS\*DIGGERS\*PULLERS\*CRANES\*SKIDDERS**

**TRACK MACHINES\*TRAILERS\*CHIPPERS\*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!**