

RENTALS. SALES AND SERVICE NEW and USED ullet AERIAL PLATFORMS ullet Digger-derrick trucks ullet Specialty equipment

HYDRAULIC PULLER—TENSIONER
THE CONDUX TESMEC AFS404 HYDRAULIC PULLER/ TEN-SIONER PROVIDES UP TO 10,100 LBS. OF PULLING AND TENSIONING FORCE. DESIGNED FOR STRINGING ONE ROPE OR ONE CONDUCTOR. INDUSTRY LEADING FEA-TURES LIKE NEGATIVE SELF—ACTING HYDRAULIC BRAKE, HYDRAULIC DYNAMOMETER, HYDRAULIC COOLING SYS-TEM AND 3 POSITION GEAR BOX. THE AFS404 HYDRAU-LICALLY CONTROLLED SYSTEM HELPS ELIMINATE CON-**DUCTOR GALLOPING, MAKING THIS ONE OF THE SAFEST** TENSIONERS ON THE MARKET TODAY. POWERED BY A 85 H.P. DIESEL ENGINE. CLOSED HYDRAULIC SYSTEM THAT **ALLOWS STEPLESS SPEED VARIATION IN BOTH DIREC-**TIONS. BULL WHEEL DIAM. 60 IN. MAX. CONDUCTOR DIAM. 1 5/16 IN. **HYDRAULIC ROPE / CONDUCTOR CLAMP FOR REEL CHANGE OPERATIONS.** 



**NEGATIVE SELF ACTING HYDRAULIC BRAKE HYDRAULIC DYNAMOMETER** HYDRAULIC OIL COOLING SYSTEM **GEAR BOX WITH 2 OPERATING POSITIONS & 1 NEUTRAL POSITION** LOW PULL/TENSION POSITION (350-1800 LBS.) HIGH PULL/TENSION POSITION (1350-10,100 LBS.) HYDRAULIC ACTUATED FRONT PLOW

## MIRK # 086P



## **PULLER PERFORMANCE:**

MAX PULL: 10,100 LBS. CONT. PULL: 1.7 MPH MAX SPEED: 3.1 MPH

**PULL AT MAX. SPEED: 5,600 LBS.** 

**TENSIONER PERFORMANCE:** MAX TENSION: 10,100 LBS. MAX SPEED: 3.1 MPH

