

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK 100,000# REEL TRAILER CHASSIS:

8'6" OVERALL WIDTH COLLAPSED
14'10" OVERALL WIDTH EXPANDED
MAXIMUM REEL CAPACITY IS 14'5" TALL
MAXIMUM REEL WIDTH IS 9'4" WIDE
LOCKING REEL WIDTHS: 7FT., 8FT, 9FT.
MAXIMUM REEL WEIGHT IS 100,000 LBS.
(TIRE RESTRICTED)
108"TALL WITH TOWERS DOWN
127" TALL WITH TOWERS UP
8'6" REEL IS THE SMALLEST LOAD AND DRIVE
EMPTY TRAILER WEIGHT IS 25,000 LBS.
25' OVERALL LENGTH
REAR REMOTE CONTROLS W/THROTTLE
RADIO REMOTE CNTRL AUTOCRANE



BODY AND ACCESSORIES:

OPENING AND CLOSING

50" GROUND TO FIRST LIFT NOTCH WALKING BEAM SUSPENSION 72" CTR. HUB AIR BRAKES

4-50 TON SPINDLE CAP STUB AXLES
9" GROUND CLEARANCE REAR 11" FRONT
LOCKABLE BOX FOR BRONZE BUSHINGS
DIAMOND PLATE CONST. STEEL FENDERS
6" WALKING BEAM TRAVEL
DOT SPEC LIGHTS AND REFLECTORS
20.5R 25 RADIAL TIRES
25X17 BUDD RIM 10 HOLE 13-3/16 SPACING
ADJUSTABLE PINTLE HITCH H.D.
2 CURBSIDE LIFT JACKS W/WHEELS TO EASE



MIRK 111K

DEUTZ F4L1011F 54 HP. 4-CYL. OIL-COOLED DIESEL
HYDRAULIC CONTROLS FOR:LIFT TOWERS EXPAND AND
RETRACT,TONGUE JACK, POWER RIM DRIVE, EX

PANDING LIFT WHEELS, ADJUST FLOW CONTROL, EXPANDING TAILGATE.

ONE SP24CDU RIM DRIVE MOTOR 16,000 INCH LBS. ONE 18"X7" EURATHANE DRIVE WHEEL W/MAN. ADJ. INDEPENDENT LIFT TOWERS FOR LEVELING REEL FIVE LOADING LOCATIONS PER LIFT TOWER X 8" PER MANUAL SPINDLE BAR LOCKING PLATES MANUAL LOCKING PINS ON ALL SLIDE COMPONENETS 7' OPEN POSITION TAKES 105" BAR- 12'8" O.A. WIDTH 8' OPEN POSITION TAKES 116" BAR- 13'8" O.A. WIDTH 9' OPEN POSITION TAKES 128" BAR- 14'8" O.A. WIDTH 2—7" BRONZE SPINDLE BAR BUSHINGS

