

**MIRK**

www.mirkinc.us

Aerial Man Lifts  
Digger Trucks**THE MIRK ADVANTAGE**

7629 Chippewa Rd • Orrville, Ohio 44667

**330-669-2000**

Fax: 330-669-3732

**RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT****CONDUX HYDRAULIC PULLER / TENSIONER**

THE CONDUX AFS 608 HYDRAULIC PULLER/ TENSIONER PROVIDES UP TO 27,500 LBS. OF PULLING AND TENSIONING FORCE. DESIGNED FOR STRINGING ONE ROPE OR CONDUCTOR. INDUSTRY LEADING FEATURES LIKE NEGATIVE SELF-ACTING HYDRAULIC BRAKE, HYDRAULIC DYNAMOMETER, HYDRAULIC COOLING SYSTEM AND 3 POSITION GEAR BOX. THE AFS 608 HYDRAULICALLY CONTROLLED SYSTEM HELPS ELIMINATE CONDUCTOR GALLOPING, MAKING THIS ONE OF THE SAFEST TENSIONERS ON THE MARKET TODAY. POWERED BY A 130 H.P. DIESEL ENGINE. CLOSED HYDRAULIC SYSTEM THAT ALLOWS STEPLESS SPEED VARIATION IN BOTH DIRECTIONS. BULL WHEEL DIAM. 60 IN. MAX. CONDUCTOR DIAM. 1.9 IN.

**MIRK # 297L CONDUX AFS608****PULLER PERFORMANCE:**

MAXIMUM PULL: 27,500 LBS.  
CONTINUOUS PULL: 20,000 LBS.  
MAXIMUM SPEED: 3.1 MPH

**TENSIONER PERFORMANCE:**

MAXIMUM TENSION: 27,500 LBS.  
CONTINUOUS TENSION: 17,868 LBS.  
MAXIMUM SPEED: 3.1 MPH

**DIMENSIONAL DATA:**

OVERALL WIDTH: 85 IN.  
OVERALL LENGTH: 178 IN.  
HEIGHT: 84 IN.  
MAXIMUM GVWR: 16,000 LBS.  
NET WEIGHT: 14,500 LBS.

NEGATIVE SELF ACTING HYDRAULIC BRAKE  
HYDRAULIC DYNAMOMETER WITH TENSION SET POINT THAT SHUTS THE MACHINE DOWN IF THE SET TENSION IS REACHED.  
HYDRAULIC OIL COOLING SYSTEM  
GEAR BOX WITH 3 OPERATING POSITIONS AND NEUTRAL POSITION (FREE-WHEEL)  
LOW TENSION POSITION ( 500-4,500 LBS. )  
NORMAL TENSION POSITION ( 2,500-27,500 LBS. )  
HYD. ACTUATED FRONT FLOW  
HYD. TOOL CIRCUITS FOR OPERATING CONDUX REEL STANDS OR RE-WINDERS. HYD. CUNDUCTOR CLAMP.



**CALL US FOR ALL YOUR EQUIPMENT NEEDS: BUCKETS\*DIGGERS\*PULLERS\*CRANES\*SKIDDERS  
TRACK MACHINES\*TRAILERS\*CHIPPERS\*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!**