

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 414W

CAB & CHASSIS SPECIFICATIONS: (MIRK STD.) **2008 INTERNATIONAL 7400 6X4** G.V.W.R. 56,000 LBS. **MAXXFORCE 10 DIESEL ENGINE (350 H.P.)** 10 SPEED MANUAL TRANS. W/ LOW/ LOW & O.D. DOUBLE LOCKING REAR DIFFERENTIAL **WIDE TRACK 16,000 LB. FRONT AXLE 40,000 LB. HENDRICKSON REAR AXLES** HAUL MAX SUSPENSION 425/65/22.5 RADIAL TIRES FRONT 11R 22.5 RADIAL TIRES REAR **HUB PILOTED BUDD WHEELS DOUBLE C CHANNEL FRAME AIR BRAKES POWER STEERING 70 GALLON FUEL TANK**



BODY SPECIFICATIONS:

ALL STEEL CONSTRUCTION FLATBED
FRONT DECK EXTENSION FOR AUGER STORAGE
(2) 18" X 48" UNDERDECK STORAGE BOXES
H.D. PINTLE STYLE HITCH
SAFETY CHAIN EYES
7 PRONG TRAILER PLUG

FRONT AXLE: 10,400 LB.
REAR AXLES: 31640 LB.
TOTAL: 42040 LB. EMPTY



PRESSURE DIGGER SPECS.

NEW WATSON MODEL 1100TM SHORT MAST JOHN DEERE 4045 DIESEL ENGINE (140 H.P.) FUNK MODEL 2000 TRANSMISSION 30 FEET OF DIGGING DEPTH ONLY 25 FT. OF MAST HEIGHT DRILL OUTPUT TORQUE UP TO 40,600 LBS. THREE ELEMENT KELLY BAR. 7" - 5" - 31/2" 4" KELLY STUB CROWD FORCE—21,300 LBS. 8500 LB. SERVICE WINCH ROTATING AND SLIDING BASE (24" OF TRAVEL) OUTRIGGERS: OUT & DOWN FRONT, STRAIGHT DOWN REARS

