RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

<u>Cab & Chassis</u>

**2003 PETERBILT 357** 

S/N: 1NPALBDX33D590463

C-15 CAT DIESEL 475 HP 6 CYLINDER W/ JACOBS BRAKE FULLER RTLO 16918B 18 SPEED MANUAL/TRANSMISSION

SEVERE SERVICE ALUMINUM CAB/ DELUXE INTERIOR/

**DELUXE SEATS/ CD PLAYER AM/FM** 

AIR CONDITIONED/ AIR HORNS/ DELUXE GAUGE PACKAGE/

HEATED CHROME MIRRORS
DOUBLE "C" CHANNEL FRAME

22,000 lb. STANDARD TRACK PT. AXLE 23,000 lb.SUSP.

46,000 lb. WIDE TRACK TANDUM REARS 4.33 RATIO

**CHALMERS 854-46,000 lb. SUSPENSION** 

10 HOLE PILOT BUDD ALCOA ALUMINUM RIMS

425/65 R 22.5 FRONT TIRES

11Rx22.5 REAR DRIVE TIRES + PUSHER AXLE

STI/ STEERABLE PUSHERS AXLE MOD HLT-10-002 (REVERSE

MOUNT)

**REAR SET UP FOR STINGER AXLE** 



**DIMENSIONS** 

**WIDTH OVERALL - 8'6"** 

**OVERALL LENGTH - 44'11"** 

**TRAVEL HEIGHT - 13'6"** 

FRONT OVERHANG - 119" (WITHOUT BUMPER EXTENTION)

**OVERALL HEIGHT MAST UP - 52'6"** 

**OVERALL WIDTH OUTRIGGERS OUT 14'6"** 

60" CLEARANCE TOP OF OUTRIGGER TO BOTTOM OF

ROTARY POT.

STEER AXLE \*1 TO PUSHER AXLE \*2 IS (117.5")

PUSHER AXLE \*2 TO DRIVE AXLE \*3 IS (145.5")

DRIVE AXLE \*3 TO DRIVE AXLE \*4 IS (54")

DRIVE AXLE #4 TO STINGER AXLE #5 IS (218")

GROSS WEIGHT: WITHOUT STINGER 68,000 lbs.

W/STINGER 72,500 lbs.

FRONT AXLE 20,720 W/PUSHER AXLE UP. DRIVES 47,220

**PUSHER UP NO STINGER** 

\*WITH STINGER AXLE COMPLETE UNIT LEGAL TO

TRANSPORT W/O PERMITS + UNDER ALL FEDERAL BRIDGE

**LAW REQUIREMENTS** 

## **MIRK #438S**



<u>MIRK MODEL 6090 DRILL RIG</u>

S/N: 6090-141

QUICK CHANGE KELLY BARS FROM 60' TO 90' DIG DEPTH 90' DIG DEPTH 8" OUTER BAR 6" INNER BAR 5/8 WALL

4" KELLY STUB 2 PIN LOCATIONS 2" + 6" 90°

**APART 1 1/8" HOLES** 

40,000 LBS. ACHIEVABLE CROWD FORCE

25,000 LBS. LINE PULL ON INNER KELLY

86,000 LBS DRILL TORQUE

PULLMASTER H-25 GROOVED DRUM INNER KELLY HOIST

M-12-12,000 Ib SERVICE WINCH

JOHN DEERE 6068T 185hp 6cyl. TURBO DIESEL ENGINE

ALLISON CRT 3531 TORQUE CONVERTER 3 SPEED

FORWARD + REVERSE POWERSHIFT TRANS. GEARED BEARING DUAL HYDRAULIC DRIVE

270° ROTATION

60" SLIDE FRAME FOR + AFT.

**OUT + DOWN FRONT OUTRIGGERS** 

**VARIABLE HEIGHT - LOW PROFILE - ANGLED HYDRAULIC** 

+ DOWN REAR OUTRIGGERS

