

MIRK

www.mirkinc.us

Aerial Man Lifts
Digger Trucks**THE MIRK ADVANTAGE**

7629 Chippewa Rd • Orrville, Ohio 44667

330-669-2000

Fax: 330-669-3732

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT**MIRK # 61 L****BULLWHEEL TENSIONER:**

WAGNER SMITH MODEL T-BWT-4-61 (FO)
TRAILER MOUNTED 61" B.O.G. DIAM. BULLWHEEL
TENSIONER. THE T-BWT-4-61(FO) IS DESIGNED
FOR LEFT HAND LAY OPGW FIBER AND ADSS FI-
BER CABLE. THE OPEN SIDED BULLWHEELS ARE
CANTED TO MINIMIZE LINE TWISTING. MAX. LINE
TENSION IS 4,000 LBS. AT UP TO 4 MPH LINE SPD
MAJOR OPERATING SAFETY FEATURES:
BULLWHEEL BRAKES ARE SMOOTH RUNNING HY-
DRAULIC CALIPERS. ALL UNIT CONTROLS
ARE LOCATED AT THE OPERATORS STATION
OFF THE GROUND, FOR OPERATOR SAFETY.
LARGE DIAMETER FAIRLEAD ROLLER ASSEMBLY
IS PROVIDED TO REDUCE BENDING RADIUS.

**TENSIONER SPECIFICATIONS:**

DIAMETER:	61" (BOTTOM OF GROVE)
GROOVE DIAMETER:	1.5"
# OF GROOVES:	3
REPLACEABLE SEG.	YES
BULLWHEEL LINING:	ELASTOMER (BOLT ON)
TENS. BRAKES:	HYD ACT. CALIPER DISC
BRAKE DISC:	42" DIAM.
BULLWHEELS:	CANTILEVERED
MAXIMUM TENSION:	4,000 LBS.
LINE SPEED (AVG.)	0—4 MPH

DIMENSIONAL DATA:

UNIT LENGTH: 17 FT. 1 1/2 IN.
UNIT WIDTH: 8 FT. 0 IN.
UNIT HEIGHT: 9 FT. 6 IN.
NET WEIGHT: 5480 LBS. (APPROX.)
SINGLE AXLE TRAILER MOUNTED
LEAF SPRING SUSPENSION
ELECTRIC BRAKES W/ BREAK A WAY
ADJ. 3" LUNETTE EYE FRONT HITCH
MECHANICAL FRONT JACK
215/75R X 17.5 RADIAL TIRES LOAD RANGE H
REAR PIN TYPE STABILIZERS
D.O.T. REGULATION LIGHTING



**CALL US FOR ALL YOUR EQUIPMENT NEEDS: BUCKETS*DIGGERS*PULLERS*CRANES*SKIDDERS
TRACK MACHINES*TRAILERS*CHIPPERS*REEL CARRIERS AND MUCH, MUCH MORE!!!!!!!**