

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

CAB & CHASSIS SPECIFICATIONS:

2019 FREIGHTLINER TANDEM CHASSIS V.I.N. 1FVKCYFE3KHKK2896 G.V.W.R. 58,000 LB. **CUMMINS L9 350 DIESEL ENGINE (350 H.P.)** TURBOCHARGED **ALLISON 6 SPD AUTOMATIC TRANS** 18,000 LB. WIDE TRACK FRONT AXLE 40,000 LB. REAR TANDEM AXLE AIR BRAKES **POWER STEERING** TILT WHEEL **AIR CONDITIONING** CRUISE CONTROL **HUB PILOTED BUDD (STEEL) WHEELS** 385/65 R22.5 RADIAL TIRES FRONT 11R22.5 RADIAL TIRES REAR L.H. 50 GAL. STEP FUEL TANK



BODY SPECIFICATIONS:

ALL STEEL CONSTRUCTION FLATBED FRONT DECK EXTENSION
(2) UNDERDECK STORAGE BOXES
H.D. PINTLE STYLE HITCH
SAFETY CHAIN EYES
7 PRONG TRAILER PLUG
AXLE WEIGHTS EMPTY:
FRONT AXLE: 10680 LBS
REAR AXLES: 33360 LBS
TOTAL: 44040 LBS

MIRK # 840J



PRESSURE DIGGER SPECS. S.N. 18234
2018 WATSON MODEL 1100TM SHORT MAST
JOHN DEERE 4045 DIESEL ENGINE (140 H.P.)
FUNK MODEL 2000 TRANSMISSION
30 FEET OF DIGGING DEPTH
ONLY 25 FT. OF MAST UP HEIGHT
DRILL OUTPUT TORQUE UP TO 40,600 LBS.
THREE ELEMENT KELLY BAR. 7" - 5" - 3 1/2"
4" KELLY STUB CROWD FORCE—21,300 LBS.
8500 LB. SERVICE WINCH
ROTATING AND SLIDING BASE (24" OF TRAVEL)
OUTRIGGERS: OUT & DOWN FRONT, STRAIGHT
DOWN REARS

