

RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

MIRK # 943H

CAB & CHASSIS SPECIFICATIONS: **2008 INTERNATIONAL 7400 6X4 CUMMINS ISM 350HP DIESEL** 10 SPEED MANUAL TRANS. W/ LOW/ LOW & O.D. **DOUBLE LOCKING REAR DIFFERENTIAL WIDE TRACK 16,000 LB. FRONT AXLE 40,000 LB. HENDRICKSON REAR AXLES** HAUL MAX SUSPENSION 425/65/22.5 RADIAL TIRES FRONT 11R 22.5 RADIAL TIRES REAR **HUB PILOTED BUDD WHEELS 3 STAGE ENGINE BRAKE** AIR CONDITIONING / AM/FM/CD **DOUBLE C CHANNEL FRAME AIR BRAKES / POWER STEERING 70 GALLON FUEL TANK**



BODY SPECIFICATIONS:

ALL STEEL CONSTRUCTION FLATBED
DECK EXTENSION SMALL AUGER STORAGE
(2) 18" X 48" UNDERDECK STORAGE BOXES
H.D. PINTLE STYLE HITCH
SAFETY CHAIN EYES
7 PRONG TRAILER PLUG

AXLE 1: 16,560 LB. AXLE 2: 21,075 LB. AXLE 3: 21,075 LB. TOTAL: 58,880

WEIGHTS:



PRESSURE DIGGER SPECS.

WATSON MODEL 2100TM
JOHN DEERE 4045 DIESEL ENGINE (140 H.P.)
CLARK 32000 TRANSMISSION
60 FEET OF DIGGING DEPTH
49 FEET OF MAST HEIGHT
TWO ELEMENT KELLY BAR 6" AND 4 1/4" WITH 4"
STUB
DRILL TORQUE—56,000 LBS.

CROWD FORCE— 24,000 LBS.
SERVICE WINCH—18,000 LBS.
OUTRIGGERS: FRONT—OUT & DOWN

DEAD A EDAME

REAR—A-FRAME

