

## RENTALS, SALES AND SERVICE NEW and USED • AERIAL PLATFORMS • DIGGER-DERRICK TRUCKS • SPECIALTY EQUIPMENT

## **MIRK # CONDUX ARS701**

## **HYDRAULIC UNDERGROUND PULLER;**

CONDUX MODEL ARS701 40,000 LB. PULLER **BULL-WHEEL DIAMETER: 23.6 INCHES NEGATIVE SELF-ACTING HYDRAULIC BRAKE HYD. DYNAMETER WITH SET POINT & AUTO. CON-**TROL OF MAXIMUM PULL. HYDRAULIC OIL COOLING SYSTEM. ON BOARD REEL WINDER WITH AUTO. LEVELWIND. HYD. QUICK CONNECTS TO CONTROL A SEPARATE REEL WINDER INSTEAD OF BUILT IN ONE. **CLOSED HYD. CIRCUIT FOR STEPLESS SPEED VARIA-**TION IN BOTH ROTATING DIRECTIONS. MACHINE IS PROVIDED WITH A PULL PRE-SETTING SYSTEM THAT MAINTAINS THE PRE SET PULLING VALUE (ALSO WHEN THE SPEED IS REDUCED TO "0") BY AUTO-MATICALLY ADJUSTING THE OPERATION SPEED AC-CORDING TO THE FRICTION AND UNEXPECTED LOADS WHICH MAY OCCUR.



OPTIONAL ELECTRONICPULL AND SPEED RECORDER REMOVEABLE OPERATOR PROTECTION SCREEN ADDITIONAL MANUAL STABILIZER JACK FOR UNDERGROUND PULLING OPERATIONS. ADJUSTABLE SIDE TO SIDE FAIRLEAD ROLLER FOR PULLING LINE. WEIGHT: 13,500 LBS. RIGID AXLE FOR TOWING AT MAX. SPEED AT 18.6 MPH WITH MECHANICAL PARKING BRAKE. 315/60R22.5 RADIAL TIRES.



## **PULLER PERFORMANCE:**

MAX PULL: 40,000 LBF SPEED @ MAX. PULL: 1.4 MPH

MAX. SPEED: 3.1 MPH

**PULL @ MAX. SPEED: 17,985 LBF** 

280 HP DIESEL ENGINE

GROUNDING CONNECTION POINT HYDRAULIC FRONT STABILIZER

